

imagePROGRAF TX-3000 PIONEERING HIGH- PERFORMANCE LARGE-FORMAT MODEL WITH STUNNING VERSATILITY.

Est. 1991
DESIGNSUPPLY
supporting creativity

The advanced 36-inch large-format inkjet ideal for CAD, GIS and Poster printing. Engineered to deliver superb precision, efficient output, reassuring security credentials and low-cost operation.



- Productive output speeds from the new print head design, and continuous printing option
- Supreme accuracy and peerless precision thanks to LUCIA TD ink
- Simple user operation, with dual-roll feeding available for the first time on a 36-inch model
- Brilliant colour gamut on plain media and superb performance on uncoated paper
- Straightforward control thanks to easy roll loading, touchscreen display and direct printing from USB
- Print to any network-connected TX-Series unit via the universal driver
- Neat and slender, the TX-3000 fits easily into compact office spaces
- Class-leading reliability, with unparalleled uptime and rock-solid security
- Take full advantage of weather-resistant media, perfect for CAD, GIS and outdoor Posters
- Bundled software helps to ensure smooth large-format-printing workflows

PRODUCT RANGE



imagePROGRAF TX-4000



imagePROGRAF TX-3000



imagePROGRAF TX-3000 MFP T36

Canon

Explore. Inspire. Improve.

TECHNICAL SPECIFICATIONS

imagePROGRAF TX-3000

TECHNOLOGY

Printer Type	5 Colour - 36"/914.4mm
Print Technology	Canon Bubblejet on Demand 6 colours integrated type (6 chips per print head x 1 print head)
Number of Nozzles	Total: 15,360 MBK: 5,120 nozzles C, M, Y, BK: 2,560 nozzles each
Print Resolution	2,400 x 1,200 dpi
Nozzle Pitch	1,200 x 2 includes Non-firing nozzle detection and compensation system
Guaranteed Minimum Line Width	0.02 mm
Line Accuracy	±0.1 % or less
Ink Droplet Size	5 Picoliter per colour
Ink Capacity	Bundled Starter Ink: 330ml (MBK)/160ml (BK,C,M,Y) Sales Ink: 160ml/330ml/700ml
Ink Type	Pigment ink: 5 colour MBK/BK/C/M/Y
OS Compatibility	Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10, Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/R2, Server 2012/R2 Apple Macintosh: OSX 10.7.5 - 10.11
Printer Languages	HP-GL/2, HP RTL, PDF, JPEG - for details check specifications
Standard Interfaces	USB B Port: Type: Built in (Hi-Speed USB) Mode: Full Speed (12 Mbit/sec), High Speed (480 Mbit/sec), Bulk transfer Connector Port: Series B (4 pins) USB A Port: USB Memory (Direct Print) Standard: IEEE 802.3 10base-T IEEE 802.3u 100base-TX/Auto-Negotiation IEEE 802.3ab 1000base-T/Auto-Negotiation IEEE 802.3x Full Duplex Protocol: SNMP (Canon-MIB, HTTP, TCP/IP (IPv4/IPv6), ftp) Wireless LAN: Standard: IEEE802.11n/IEEE802.11g/IEEE802.11b Security: WEP (64/128bit) WPA-PSK (TKIP/AES) WPA2-PSK (TKIP/AES)
MEMORY	
Standard memory	128GB (Physical memory 2GB)
Expansion slot	No
HARD DISK	
	500GB (Encrypted)
PAPER HANDLING	
Media Width	Roll paper: 8"/203.2mm - 36"/914.4mm Cut sheet: 8"/203.2mm - 36"/914.4mm
Media Thickness	0.07 - 0.8mm
Minimum Printable Length	203.2mm
Maximum Printable Length	Roll Paper: 18m (varies according to the OS and application) Cut Sheet: 1.6m
Maximum Media Roll Diameter	170 mm
Paper Feed Method	Roll Paper: Front loading, front output Cut Sheet: Front loading, front output (Manual feed using media locking lever)

Borderless Printing Width (Roll Only)

[Recommended] 515mm(JIS B2), 594mm(ISO A1) 728mm (JIS B1), 841mm (ISO A0), 10", 14", 17", 24", 36"
[Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm(ISO A3+), 420mm(ISO A2), 8", 12", 16", 20", 30", 300mm, 500mm, 600mm, 800mm

DIMENSIONS AND WEIGHT

Physical Dimensions - (W x D x H)

Printer unit with basket open and printer stand: 1389 x 984 x 1168 mm (Basket Open)
Weight: 105 kg (including Roll Holder)

Software Included

imagePROGRAF TX-Series Printer Driver, Print Plug-In for Office, Quick Utility Toolbox and PosterArtist Lite
Other software available as Download from Web.

POWER AND OPERATING REQUIREMENTS

Power Supply

Input Power: AC 100-240 V (50-60 Hz)

Power Consumption

Power consumption (using wired LAN): 105 W or less
At sleep mode (using wired LAN): 3.6 W or less
At sleep mode (using all ports): 3.6 W or less
<EU only - data for ErP Lot 26>
At the power off: 0.3 W or less
Default setting for the time to enter the Sleep mode: 301sec
<EU only - data for ErP Lot 26>

Operating Environment

15 - 30°C, 10 - 80 % (Condensation free)

Noise Level (Approx.)

Operation : 51dB(A) or less
(Plain paper, line drawing, standard mode)
Stand by : 35dB(A) or less
(Measured on ISO7779 standard)

Regulations

Europe: CE mark

Environment Certificates

Russia: EAC, Other Countries: CB certification
ENERGY STAR (WW), RoHS directive, IT ECO Declaration (Europe), WEEE

WHAT'S INCLUDED

What's in the Box?

Printer, 1 x Print Head, 1 x Maintenance Cartridge, 3" Paper Core Attachment, EU & UK Power Cable, 1 Set of Starter Ink Tanks, Set Up Guide, Safety/Standard, Software CD-ROM (OSX/Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Print head Alignment Sheet

OPTIONS

Optional Items

Roll Unit: RU-32
Stacker: SS-31
2/3" Roll Holder: RH2-34

CONSUMABLES

User Replaceable Items

Print Head: PF-06
Ink Tanks: PFI-110
Cutter Blade: CT-07
Maintenance Cartridge: MC-30

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and R: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



Est. 1991

DESIGNSUPPLY
supporting creativity

Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition

© Canon Europa N.V., 2017



0800 018 23 23

sales@designsupply.com

Explore. Inspire. Improve.