



HP DesignJet T790 Printer series

The most productive 24-inch HP DesignJet printer¹ for small teams



QUALITY—Quickly produce outstanding results

- Six Original HP inks produce a wide color gamut ideal for color graphics.
- Original HP gray and photo black inks achieve precise line accuracy, dark blacks, and true neutral grays.
- Communicate with precision—produce plans, drawings, and maps with fine line quality, and up to 2400 dpi.
- Print quickly without sacrificing quality—create an A1/D-size print in 32 seconds with Economode.

CONVENIENCE—Speed up printing with easy workflow

- Print TIFF, JPEG, and PDF² files from your printer's USB thumb drive—no computer required.
- If you're on-the-go, attach your document to an email and send it directly to your printer via ePrint.³
- The intuitive touchscreen simplifies navigation and printing.

RELIABILITY—Plug-and-play printer for small teams

- Focus on your design—not printing—with this reliable HP DesignJet printer.
- Quick printing—in-printer processing architecture, added memory for processing even the most complex files.
- Print confidently knowing that, even if you're in a rush, this printer can handle all your files.

For more information, please visit
hp.com/go/designjetT790

¹ Compared to other 24-inch HP DesignJet T-series printers.

² PDF files only available with PostScript® (PS) accessory (optional accessory to be purchased separately) or with the PostScript® version of the printer.

³ Local printing requires mobile device and printer to be on the same network (usually Wi-Fi access points bridge wireless to wired connections) or have a direct wireless connection. Wireless performance is dependent on physical environment and distance from access point. Wireless operations are compatible with 2.4 GHz operations only. Remote printing requires an Internet connection to an HP web-connected printer. Wireless broadband use requires separately purchased service contract for mobile devices. Check with service provider for coverage and availability in your area. See <http://www.hp.com/go/designjetmobility> for more details.

Technical specifications

Print	Line drawings ⁴	32 sec/page on A1/D, 93 A1/D prints per hour	
	Colour images ⁵	Fast: 37 m ² /hr (400 ft ² /hr) on coated media Best: 2.8 m ² /hr (30 ft ² /hr) on glossy media	
	Print resolution	Up to 2400 x 1200 optimized dpi from 1200 x 1200 input dpi and Optimization For Photo Paper selected	
	Margins (top x bottom x left x right)	Roll: 5 x 5 x 5 x 5 mm (0.2 x 0.2 x 0.2 x 0.2 in) Sheet: 5 x 17 x 5 x 5 mm (0.2 x 0.67 x 0.2 x 0.2 in)	
	Technology	HP Thermal Inkjet	
	Ink types	Dye-based (C, G, M, pK, Y); pigment-based (mK)	
	Ink drop	6 pl (C, G, M, pK); 9 pl (mK, Y)	
	Printheads	3 (G & pK, mK & Y, M & C)	
	Line accuracy	+/- 0.1% ⁶	
	Minimum line width	0.02 mm (0.0008 in) (HP-GL/2 addressable)	
	Guaranteed minimum line width	0.06 mm (0.0024 in) (ISO/IEC 13660:2001(E)) ⁷	
	Media	Handling	Sheet feed, roll feed, automatic cutter
		Weight	60 to 328 g/m ²
Size		210 to 610-mm (8.3 to 24-in) wide sheets; 279 to 610-mm (11 to 24-in) rolls	
	Thickness	Up to 0.8 mm (31.5 mil)	
	Memory	Basic Printer	8 GB (virtual) ⁸
PostScript [®] Printer		8 GB (virtual) ⁸ , 160 GB hard disk	
Connectivity	Interfaces (standard)	Fast Ethernet (100Base-T), Hi-Speed USB 2.0 certified, EIO Jetdirect accessory slot	
	Print languages (standard)	Basic Printer: HP-GL/2, TIFF, JPEG, CALS G4, HP PCL 3 GUI PostScript[®] Printer: Adobe [®] PostScript [®] 3 [™] , Adobe PDF 1.7, HP-GL/2, TIFF, JPEG, CALS G4, HP PCL 3 GUI	
	Print languages (optional)	Basic Printer: Adobe PostScript 3, Adobe PDF 1.7	
	Drivers (included)	HP-GL/2, HP-RTL drivers for Windows [®] (optimized for AutoCAD 2000 and higher); HP PCL 3 GUI driver for Mac OS X; PostScript Windows, Linux, and Mac drivers ⁹	
Dimensions (w x d x h)	Printer	1262 x 702 x 1050 mm (49.7 x 27.6 x 41.3 in)	
	Shipping	1440 x 766 x 770 mm (56.7 x 30.2 x 30.3 in)	
Weight	Printer	60 kg (132 lb)	
	Shipping	77 kg (170 lb)	
What's in the box:	HP DesignJet T790 Printer, printheads, introductory ink cartridges, printer stand ¹⁰ , spindle, quick reference guide, setup poster, startup software, power cord		
Environmental ranges	Operating temperature:	5 to 40°C (41 to 104°F)	
	Storage temperature:	-25 to 55°C (-13 to 131°F)	
	Operating humidity:	20 to 80% RH	
Acoustic	Sound pressure:	43 dB(A) (active); 29 dB(A) (standby)	
	Sound power:	6.1 B(A) (active); 4.7 B(A) (standby)	
Power consumption		< 120 watts (printing), < 27 watts (ready), < 7 watts (< 25 watts with embedded Digital Front End) (sleep), 0.1 watts (off)	
	Input voltage (auto ranging)	100 to 240 VAC (+/- 10%), 50/60 Hz (+/- 3 Hz), 2 A max	
Certification	Safety	USA and Canada (CSA certified), EU (LVD and EN60950-1 compliant), Russia (GOST), Singapore (PSB), China (CCC), Argentina (IRAM), Mexico (NYPE), Korea (KATS)	
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI), Korea (KCC)	
	Environmental	ENERGY STAR, WEEE, EU RoHS, China RoHS, REACH, FEMP, EPEAT Bronze	
Warranty	One-year limited hardware warranty		

Eco Highlights

- ENERGY STAR[®] qualified and EPEAT Bronze registered¹
- Free, convenient HP ink cartridge and printhead recycling²
- FSC[®]-certified papers and a range of recyclable HP media with a take-back program²

¹ EPEAT registered where applicable and/or supported. See epeat.net for registration status by country.

² Program availability varies. Please check hp.com/recycle for details. BMG trademark license code FSC[®]-C115319, see fsc.org. HP trademark license code FSC[®]-C017543, see fsc.org. Not all FSC[®]-certified products are available in all regions. For information about HP large format printing materials, please visit HPLFMedia.com.

Please recycle large-format printing hardware and printing supplies

Find out how at our website
hp.com/ecosolutions



© Copyright 2012, 2015 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.

Adobe, PostScript, and Adobe PostScript 3 are trademarks of Adobe Systems Incorporated. Windows is a U.S. registered trademark of Microsoft Corporation. Mac and the Mac logo are trademarks of Apple Computer, Inc., registered in the U.S. and other countries.

4AAA-1679EEW, November 2015, Rev.1

Ordering information

Product	CR647A ⁹	HP DesignJet T790 24-in Printer	
	CR648A	HP DesignJet T790 24-in PostScript Printer	
Accessories	CN538A	HP DesignJet 3-in Core Adapter	
	CN500B	HP DesignJet PostScript Upgrade	
	CQ783A	HP DesignJet T7xx 24-in Spindle	
	Q6663A	HP DesignJet T/Z 24-in Stand ¹¹	
	CQ654C	HP DesignJet HD Scanner	
	J8025A	HP Jetdirect 640n Print Server	
	A9D02A	SCP reprocontrol with Folder Driver for HP	
	Original HP printheads	C9380A	HP 72 Gray and Photo Black Printhead
		C9383A	HP 72 Magenta and Cyan Printhead
		C9384A	HP 72 Matte Black and Yellow Printhead
Original HP ink cartridges	C9397A	HP 72 69-ml Photo Black Ink Cartridge	
	C9398A	HP 72 69-ml Cyan Ink Cartridge	
	C9399A	HP 72 69-ml Magenta Ink Cartridge	
	C9400A	HP 72 69-ml Yellow Ink Cartridge	
	C9401A	HP 72 69-ml Gray Ink Cartridge	
	C9403A	HP 72 130-ml Matte Black Ink Cartridge	
	C9370A	HP 72 130-ml Photo Black Ink Cartridge	
	C9371A	HP 72 130-ml Cyan Ink Cartridge	
	C9372A	HP 72 130-ml Magenta Ink Cartridge	
	C9373A	HP 72 130-ml Yellow Ink Cartridge	
	C9374A	HP 72 130-ml Gray Ink Cartridge	
	Original HP large format printing materials	C6035A	HP Bright White Inkjet Paper (FSC [®] certified) ¹² ♻️ ¹³ 610 mm x 45.7 m (24 in x 150 ft)
		C6019B	HP Coated Paper (PEFC [™] certified) ¹² ♻️ ¹³ 610 mm x 45.7 m (24 in x 150 ft)
		C6029C	HP Heavyweight Coated Paper (PEFC [™] certified) ¹² ♻️ ¹³ 610 mm x 30.5 m (24 in x 100 ft)
CZ987A		HP Premium Satin Photo Paper (FSC [®] certified) ¹² 610 mm x 15.2 m (24 in x 50 ft)	
Service and support	HP596E	HP 3 year Next Business Day Onsite Support	
	HP603E	HP 3 year Next Business Day Onsite Support with Defective Media Retention ¹⁴	
	HP598E	HP 3 year 4-hour response, 13x5 Onsite Support ¹⁵	
	HP597E	HP 3 year 4-hour response, 9x5 Onsite Support ¹⁵	
	HP603E	HP 3 year Next Business Day Onsite Support with Defective Media Retention ¹⁴	
	HP993PE	HP 1 year Post Warranty, Next Business Day Onsite Support	
	HP995PE	HP 1 year Post Warranty, Next Business Day Onsite Support with Defective Media Retention ¹⁵	
	HP997PE	HP 1 year Post Warranty, 4-hour response, 13x5 Onsite Support ¹⁵	
	H4518E	HP Network Installation Service	
	H7604E	HP Installation and Startup Service	

HP DesignJet Support Services offer solutions for business critical environments — installation, extended support and maintenance, as well as variety of value added services. For more information, please visit hp.com/go/designjetsupport.

Use **Original HP inks** and printheads to experience consistent high quality and reliable performance that enable less downtime. These critical components are designed and engineered together as an optimized printing system to provide precise line accuracy as well as dark blacks and true neutral grays¹⁶. For more information, visit hp.com/go/OriginalHPInks.

For the entire **HP Large Format Printing Materials** portfolio, please see HPLFMedia.com.

⁴ Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper (Bond) with Original HP inks.

⁵ Mechanical printing time with Original HP inks.

⁶ +/-0.1% of the specified vector length or +/-0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Matte Film and Original HP inks.

⁷ Measured on HP Matte Film.

⁸ Based on 640 MB RAM.

⁹ Included with PostScript printers only.

¹⁰ Only available in Asia Pacific, Japan, and Latin America.

¹¹ Stand not included in the box outside of North America and Latin America.

¹² FSC[®] trademark license code FSC[®]-C017543, see fsc.org. PEFC[™] trademark license code PEFC[™]/29-31-198, see pefc.org. Not all FSC[®]- or PEFC[™]-certified products are available in all regions.

¹³ Can be recycled through commonly available recycling programs.

¹⁴ Not available in Europe, Middle East, and Africa.

¹⁵ Not available in North America and Latin America.

¹⁶ Applicable to HP DesignJet T-series Printers, Printers, and eMFPs. True neutral grays produced by printers compatible with the HP Three-black ink set.

Est. 1991
DESIGN SUPPLY
supporting creativity

0800 018 23 23

sales@designsupply.com