KEY FEATURES

- 5m/16ft a minute
- Variable speed control
- Foot pedal
- Reverse mode
- Multilingual control panel
- 15mm/0.6" mounting thickness

GREAT FOR USE IN

- Sign makers
- Print finishers

IDEAL WHEN LAMINATING

- Posters, graphics and signs
- Mounting prints to board
- Applying vinyls, tapes and adhesive films

and many more...

Scan with your smartphone to watch







Design & Performance

The Easymount® laminators are designed to perform and built to last.

Their advanced features allow you to laminate and mount.

Designed in-house by Vivid, the Easymount® range gives your business extra capacity by allowing you to offer your customers a complete service that you previously had to outsource.

Specifications	EM-650SHW
Laminating Speed (m/ft/min)	5m/16ft
Max. Width (mm/inches)	650mm/26"
Mounting Thickness (mm/inches)	15mm/ 0.6"
Roller Diameter (mm/inches)	65mm/2.5"
Laminating Temperature (°C/°F)	0-130°C
Control Panel	LED
Pressure Adjustment	Manual/Gauge
Film Cara (mm/inchas)	77mm /2"

•	
_aminating Speed (m/ft/min)	5m/16ft
Max. Width (mm/inches)	650mm/26"
Mounting Thickness (mm/inches)	15mm/ 0.6"
Roller Diameter (mm/inches)	65mm/2.5"
_aminating Temperature (°C/°F)	0-130°C
Control Panel	LED
Pressure Adjustment	Manual/Gauge
Film Core (mm/inches)	77mm/3"
Power Supply AC (V–Hz)	220/240-50-60
Power Consumption (W)	50
Overall Dimensions (mm/inches)	850x300x470mm/33x12x19"
Gross Machine Weight (Kg/lbs)	76Kg/168lbs
Warranty	1 year







Mode

Features

- Solid heavy duty construction
- Release liner take-up
- Adjustable rollers up to 15mm/0.6"
- Handy reverse mechanism
- Foot pedal for controlled operation

