



## imagePROGRAF GP-6600S

# PRECISION PALETTE, CRAFTING BRILLIANCE

A revolution in printing premium posters for chain retail & franchised stores, as well as print service providers with a sustainable 60" large format printer – where accuracy meets vibrancy. Unlock an eye-catching spectrum of colours with PANTONE™<sup>1</sup> precision, thanks to the innovative new LUCIA PRO II ink<sup>3</sup>, especially orange ink. Get sustained productivity without compromising on image quality and longevity.

- **Professional image quality**

Dive into a world of vivid corporate colours that captivate, paired with enhanced black density that brings more depth to your premium posters. The imagePROGRAF GP-6600S goes beyond ink – it provides total colour accuracy, perfect colour gradation and highlights a wide PANTONE™ coverage<sup>2</sup>

- **Increased durability**

Preserve your premium posters for 200 years<sup>4</sup> with better light fastness using high light-resistance ink. Improve image robustness with high scratch resistant ink helps ensure your prints last a lifetime

- **Enhanced productivity**

Transform printing workflows with easier media handling and simplified settings. Enhance efficiency with dual rolls, auto media loading, mirrored ink arrangement with high speed printing. With new print head monitoring function and auto alignment adjustment, masterpieces are created with confidence without image deterioration

- **Improved sustainability**

Protect the environment by using less power during both operation and power-off. It is EPEAT Gold rated<sup>5</sup> and its packaging reduces 89.5% of polystyrene usage<sup>6</sup>

<sup>1</sup>PANTONE™ is a trademark or registered trademark of Pantone LLC.

<sup>2</sup>PANTONE FORMULA GUIDE Solid Coated colour gamut coverage rate is 96% for GP-6600S/4600S/2600S, when using Premium Semi-Glossy Paper 2 with imagePROGRAF printer driver at [High] [Color Correction Off]; coverage rate is 82% when using Heavyweight Coated Paper HG with imagePROGRAF printer driver at [High] [Color Correction Off]

<sup>3</sup>Five of the seven inks are newly developed. The matte black and orange inks are the same as those used by the imagePROGRAF GP-2000/4000.

<sup>4</sup>When using Canon Heavyweight Coated Paper HG 145gsm. Predicted value calculated in accordance with the indoor light resistance test method and life evaluation criteria of the digital colour photographic print image preservation evaluation method (JEITA CP-3901B) published by JEITA (Japan Electronics and Information Technology Industries Association).

<sup>5</sup>EPEAT Gold registered in the U.S.

<sup>6</sup>58.9% reduction of polystyrene in packaging if second roll unit is included.

# TECHNICAL SPECIFICATIONS

# imagePROGRAF GP-6600S

|   |   |
|---|---|
| <b>PRINTER TECHNOLOGY</b>                       |   |
| <b>Printer Type</b>                             | 7 Colours 60"   |
| <b>Print Technology</b>                         | Canon Bubblejet on Demand 12 colours integrated type (12 chips per print head x 1 print head)   |
| <b>Print Resolution</b>                         | 2,400 x 1,200 dpi   |
| <b>Number of Nozzles</b>                        | 18,432 nozzles (MBK/C/M/Y/O:1536nozzles x2, PBK/GY:1536nozzles x1)  |
| <b>Line Accuracy</b>                            | ±0.1% or less<br>User adjustments necessary. Printing environment and media must match those used for the adjustments.  |
| <b>Nozzle Pitch</b>                             | 600 dpi x 2 Includes Non-firing nozzle detection and compensation system  |
| <b>Ink Droplet Size</b>                         | minimum 4pl per colour  |
| <b>Ink Capacity</b>                             | Bundled Starter Ink: 2310ml (330ml for each colour)<br>Sales Ink: 160ml / 330ml / 700ml   |
| <b>Ink Type</b>                                 | Pigment inks : 7 colours (Matte Black, Photo Black, Cyan, Magenta, Yellow, Grey, Orange)  |
| <b>OS Compatibility</b>                         | 32 Bit: Windows 7, Windows 8.1, Windows 10<br>64 Bit: Windows 7, Windows 8.1, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022<br>Apple Macintosh: macOS 10.15.7-macOS 13                                    |
| <b>Others supported job submission protocol</b> | Apple AirPrint  |
| <b>Printer Languages</b>                        | PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)  |
| <b>Standard Interfaces</b>                      | USB A Port: USB Memory (Direct Print) for PDF/JPEG files<br>USB B Port: Hi-Speed USB<br>Ethernet: IEEE802.3ab(1000base-T), IEEE802.3u(100BASE-TX)/IEEE802.3 (10BASE-T)<br>Wireless LAN <sup>1</sup> : IEEE802.11n/IEEE802.11g/IEEE802.11b |
| <b>MEMORY</b>                                   |   |
| <b>Standard Memory</b>                          | 3GB<br>Expansion slot : No  |
| <b>Hard Drive</b>                               | 500 GB (Encrypted HDD)  |
| <b>PRINTING SPEED</b>                           |   |
|   | Plain paper (A0):<br>0:48 (Level 5)   |
|   | Coated paper (A0)<br>1:24 (Fast)<br>2:24 (Standard)   |
|   | Glossy Photo Paper (A0)<br>2:56 (Fast)<br>4:44 (Standard)   |
| <b>MEDIA HANDLING</b>                           |   |
| <b>Media Feed and Output</b>                    | Upper Roll Paper : One Roll, Upper-loading, Front Output<br>Lower Roll Paper: One Roll, Upper-loading, Front Output<br>Cut Sheet : Upper-loading, Front Output<br>(Manual feed using media locking lever)                                 |
| <b>Media Width</b>                              | Roll paper: 152.4 - 1524mm<br>Cut sheet: 152.4 - 1524mm   |
| <b>Media Thickness</b>                          | Roll/Cut : 0.07mm - 0.8mm   |
| <b>Minimum Printable Length</b>                 | Roll paper: 101.6mm (Cross and canvas paper: 200mm)<br>Cut sheet: 203.2mm   |
| <b>Maximum Printable Length</b>                 | Roll paper : 18m (varies according to the OS and application)<br>Cut sheet : 1.6m   |
| <b>Maximum Media Roll Diameter</b>              | 170mm   |
| <b>Media Core Size</b>                          | Internal diameter of roll core: 2"/3"   |
| <b>Margins Recommended area</b>                 | Roll paper: Top: 20mm, Bottom: 3mm, Side: 3mm<br>Cut sheet (Others): Top: 20mm, Bottom: 20mm, Side: 3mm   |

|  |   |
|--|---|
| <b>Margins Printable area</b>                | Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm<br>Roll paper (borderless): Top: 0mm, Bottom: 0mm, Side: 0mm<br>Cut sheet: Top: 3mm, Bottom: 12.7mm, Side: 3mm   |
| <b>Media Feed Capacity</b>                   | Roll Paper: Two rolls. Automatic switching is possible<br>Roll Paper, Cut Sheet: Manual switching is possible<br>Cut Sheet: 1 sheet   |
| <b>Media Take-Up Roll Unit</b>               | Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll   |
| <b>Borderless Printing Width (Roll Only)</b> | [Recommended] 515mm(JIS B2), 728mm(JIS B1), 1030mm(JIS B0), 594mm(ISO A1), 841mm(ISO A0), 10", 14", 17", 24", 36", 42", 44", 50", 54", 60"<br>[Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm(ISO A3+), 364mm(JIS B3/B4), 420mm(ISO A2), 6", 8", 12", 15", 16", 18", 20", 22", 30", 34", 300mm, 500mm, 600mm, 800mm, 1000mm<br>Other than above, free size borderless printing is supported on only roll paper by user definition |
| <b>Maximum number of delivered prints</b>    | Standard position: 1 sheet<br>Flat position: A2 landscape, glossy paper less than 10 sheets, coated paper less than 20 sheets (excludes strong curled condition)  |
| <b>POWER AND OPERATING REQUIREMENTS</b>      |   |
| <b>Power Supply</b>                          | AC 100-240V (50-60Hz)   |
| <b>Power Consumption</b>                     | Operation: 94W or less<br>Sleep mode: 2.2W or less<br>Default setting for the time to enter the Sleep mode: Approx. 5 minutes<br>Power off: 0.1W or less  |
| <b>Operating Environment</b>                 | Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)   |
| <b>Acoustic Noise (Power/Pressure)</b>       | Operation: Approx. 49dB(A) (Measured based on ISO7779 Photo Glossy Paper HG/Standard/60")<br>Standby: 35 dB(A) or less  |
| <b>Regulations</b>                           | Operation: 6.6 Bels or less (Measured based on ISO7779 Photo Glossy Paper HG/Standard/60")  |
| <b>Environment Certificates</b>              | CE mark, UKCA mark<br>CB certification, EPEAT GOLD <sup>2</sup>   |
| <b>DIMENSIONS AND WEIGHT</b>                 |   |
| <b>Physical Dimensions and Weight</b>        | W x D x H<br>Main unit + Stand<br>1999×984×1168 mm (Basket Opened)<br>1999×766×1168 mm (Basket Closed)<br>169 kg (including Roll Holder Set, excluding ink and print head)  |
| <b>Packaged Dimensions and Weight</b>        | Printer (Main unit with pallet): 2227 x 915 x 1025 mm, 218kg<br>Roll unit: 2133 x 562 x 461 mm, 42kg  |
| <b>WHAT'S INCLUDED</b>                       |   |
| <b>What's in the Box?</b>                    | Printer, Printer Stand, 1 Print head, Power Cable, 1 Set of starter ink tanks, Installation Guide, Safety/Standard Environment leaflet, LFP Eur Address Sheet, Important Information Sheet, Stack Printer Stand Setup Guide, Notice for PosterArtist WEB<br>Software available as Download from Web.  |
| <b>Software Included</b>                     |   |
| <b>OPTIONS</b>                               |   |
| <b>Optional Items</b>                        | 2"/3" Roll Holder: RH-26<br>Roll Unit: RU-63  |
| <b>CONSUMABLES</b>                           |   |
| <b>User Replaceable Items</b>                | Ink Tank: MBK/Orange: PFI-2100(160ml)/PFI-2300(330ml)/PFI-2700(700ml)<br>Others: PFI-3100(160ml)/PFI-3300(330ml)/PFI-3700(700ml)<br>Print Head: PF-10<br>Cutter Blade: CT-07<br>Maintenance Cartridge: MC-30  |

<sup>1</sup>Please refer to user manual how to activate/deactivate the wireless LAN

<sup>2</sup>EPEAT Gold registered in the U.S.

## Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice™ and ™. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



E | sales@designsupply.com  
T | 020 7842 1555 W | www.designsupply.com  
Unit 2, Green Lane Business Centre, New Eitham, London, SE9 3TL